

No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 1 of 8

CUSTOMER NAME: FOSHAN YAJ BUILDING CO., LTD

ADDRESS: JINXIAN ROAD, HE SHUN, LISHUI TOWN, NAN HAI DISTRICT,

FOSHAN CITY, GUANGDONG PROVINCE, P.R.CHINA

Sample Name : rock wool sandwich panel Product Specification : 50mm sandwich panel,

pre-painted steel sheet 0.45mm thick,

rock wool density 105kg/m3

Manufacturer : FOSHAN YAJ BUILDING CO., LTD

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Date of Receipt : Apr 23, 2018
Testing Start Date : Apr 23, 2018
Testing End Date : Jun 20, 2018

Test result(s) : For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to

the sample(s) tested)

Signed for SGS-CSTC Standards Technical Services Co., Ltd. GZ Branch Testing Center

Salon Liu

Authorized signatory





No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 2 of 8

Test Result Summary

Test(s) Requested	Result(s)
EN 13501-1:2007+A1:2009	Classification: A2-s1, d0
Summary:	-
1. For further details, please refer to the following page(s).	





No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 3 of 8

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2007+A1:2009 Fire classification of construction products and building elements -Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- 1. EN 13823:2010+A1:2014 Reaction to fire tests for building products Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 1716:2010 Reaction to fire tests for products -Determination of the gross heat of combustion. (Calorific Value)

Mounting and fixing (For EN 13823:2010+A1:2014):

The specimen was tested free standing at a distance of at least 80 mm from the backing board. Both wings were clamped at the top and the bottom.

Test Results:

Test method	<u>Parameter</u>	Number of tests	<u>Results</u>
EN ISO 1716:2010	For external non-substantial component (Coating): Heat of Combustion -PCS (MJ/m2)		
	For internal non-substantial component (glue): Heat of Combustion -PCS (MJ/m2)		1.0
	For substantial components (rock wool): Heat of Combustion -PCS (MJ/kg)		1.5
	For substantial component (<u>Aluminum panel</u>): Heat of Combustion -PCS (MJ/kg)		
	The product as a whole: Heat of Combustion -PCS (MJ/kg)		0.5
EN 13823:2010+A1: 2014	FIGRA _{0.2MJ} (W/s)		35.9
	THR _{600s} (MJ)	3	2.9
	SMOGRA (m²/s²)		1.7
	TSP _{600s} (m ²)		7.5
	LFS < edge of specimen		Yes
	Flaming particles or droplets		No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s] For the classes A2 and B, FIGRA $_{0.2}$ MJ

For the classes C and D, FIGRA_{0.4}MJ

LFS -Lateral flame spread [m]

THR_{600s}-Total heat release within 600 s [MJ]

SMOGRA -Smoke growth rate [m²/s²]

TSP_{600s} -Total smoke production within 600 s [m²]

PCS -gross heat of combustion [MJ/kg or MJ/m²]



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints werefad, available on request or accessible at http://www.sgs.com/en/terms-and-Conditions.aspx.and, for electronic format document ubject to Terms and Conditions (Ferms-e-Document as) taken to the limitation of liability, indemnification and jurisdiction issues defined therad-Conditions/Terms-e-Document.asp taken to the limitation of liability, indemnification and jurisdiction issues defined therad-Conditions/Terms-e-Document.asp taken to the limitation of liability, indemnification and jurisdiction issues defined therad-Conditions/Terms-e-Document.asp taken to the company's findings at the time of its intervention only and within the limits client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forger faisification of the content uppearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the 30 days only.

198 Kezhu Road, Scientech Park, Economic & Technical Development District, Guangzhou, China. 510663 t (86-20) 82155555 f (86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮第: 510663 t (86-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com



No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 4 of 8

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2007+A1:2009.

Classification:

Fire behaviour	Smoke p	roduction		Flaming	droplets
A2	s	1	,	d	0

Remark:

The classes with their corresponding fire performance are given in Table 1.

Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product.

The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.





No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 5 of 8

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe

thermal insulation products.

Class	Test method(s)		Classification criteria	Additional classification
	EN ISO 1182 a and		<i>ΔT</i> ≤30°C, and	-
A1			⊿ <i>m</i> ≤50%, and	
			t _f =0(i.e. no sustained flaming)	
	EN ISO 1716		PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{b c} and PCS≤1.4MJ/m ^{2 d} and PCS≤2.0MJ/kg ^e	-
A2	EN ISO 1182 ^a or and		<i>∆T</i> ≤50°C, and	
		and	<i>∆m</i> ≤50%, and t _i ≤20 s	-
	EN ISO 1716		PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ² b and PCS≤4.0MJ/m ² d and PCS≤3.0MJ/kg ^e	-
	EN 13823		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR_{600s}≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
В	EN 13823 and		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 ⁱ Exposure =30s		Fs≤150mm within 60 s	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at http://www.sgs.com/en/terms-and-Conditions.aspx and, for electronic format document subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.asp; Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of his document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits cilient's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce secept in full, without prior written approval of the Company. Any unauthorized alteration, forger faisflication of the content appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the Jaw. Unless otherwise stated the seults shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

18/8 Katu Road, Scientech Park, Economic & Technical Development District, Guangzhou, China. 510663 t (88-20) 82155555 f (88-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮錦: 510663 t (88-20) 82155555 f (88-20) 82075080 e sgs.china@sgs.com



No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 6 of 8

С	EN 13823 and	FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 LEXPOSURE=30s	Fs≤150mm within 60 s	
D	EN 13823 and	FIGRA≤750W/s	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 i Exposure=30s	Fs≤150mm within 60 s	
Е	EN ISO 11925-2 ⁱ Exposure =15s	Fs≤150mm within 20 s	flaming droplets/particles h
F	No performance determined		

^a For homogeneous products and substantial components of non-homogeneous products.

- $s1 = SMOGRA \le 30m^2/s^2$ and $TSP_{600s} \le 50m^2$; $s2 = SMOGRA \le 180m^2/s^2$ and $TSP_{600s} \le 200m^2$; $s3 = not \ s1$ or s2
- g d0 = No flaming droplets/ particles in EN 13823 within 600 s;
- d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s; d2 = not d0 or d1.
- Ignition of the paper in EN ISO 11925-2 results in a d2 classification.
- h Pass = no ignition of the paper (no classification);
- Fail = ignition of the paper (d2 classification).
- Under conditions of surface flame attack and, if appropriate to the end-use application of the product, edge flame attack.

SAMPLE INFORMATION AND PICTURES

Thickness; About 50mm
Area density of the product: About 12.1kg/m²

Area density of the coating: 66g/m²(Provided by the client)
Area density of the glue: 40g/m²(Provided by the client)



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed verteral, available on request or accessible at http://www.gsg.com/en/Terms-and-Conditions.aspx and relectronic format documents, ubject to Terms and Conditions for Electronic Documents at http://www.gsg.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Itention is drawn to the limitation of ilability, indemnification and jurisdiction issues defined therein Any holder of this document is dvised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of illent's instructions, if any. The Company's sole responsibility is to its Client and this document so not exonerate parties to a ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approved of the Company. Any unauthorized alteration, forgery or falsification of the content or ppearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the souths shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30x yonly.

198 Kezhu Road, Scientech Park, Economic & Technical Development District, Guangzhou, China. 510663 t (86-20) 82155555 f (86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 鄭錦: 510663 t (86-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com

^b For any external non-substantial component of non-homogeneous products.

^c Alternatively, any external non-substantial component having a PCS ≤ 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA ≤ 20 W/s, and LFS < edge of specimen, and THR_{600s} ≤ 4,0 MJ, and s1, and d0.

d For any internal non-substantial component of non-homogeneous products.

^e For the product as a whole.

In the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production.



No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 7 of 8



Before test (for EN 13823)



After test (for EN 13823)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/terms-and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/terms-and-Conditions/Terms-e-Document.apx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery classification appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this text report refer only to the sample(s) tested and seuch sample(s) are retained for 30 days only.

 1443, or email: CN. Doccheck@egs.com

 198 Karuh Rod, Schienbar Ent. Exonica fielderal Development District, Guangzhou, Chira.
 510663
 t (86-20) 82155555
 f (86-20) 82075080
 www.sgsgroup.com.cn

 中国・广州・经济技术开发区科学城科珠路198号
 邮编: 510663
 t (86-20) 82155555
 f (86-20) 82075080
 e sgs.china@egs.com



No.: GZIN1804019402CM

Date: Jun 20, 2018

Page: 8 of 8





Coating







Rock wool Aluminum panel
Note: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch.

****** End of report******



ant District, Guangzhou, China. 510663 t (86-20) 82155555 f (86-20) 82075080 www.sgsgroup.com.cn ≰198号 鄭第: 510663 t (86-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com 中国・广州・经济技术开发区科学城科珠路198号